



N=NUMBER OF CONTACT

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	YCH 12/10/07'	~	

- NOTES:
- MATERIAL
 - INSULATOR:THERMOPLASTIC(UL 94V-0).
 - CONTACT MATERIAL: COPPER ALLOY.
 - SPECIFICATION
 - CURRENT RATING:1.5 A.
 - INSULATION RESISTANCE:1000MΩ Min.
 - DIELECTRIC WITHSTANDING:600VAC.
 - CONTACT RESISTANCE:20mΩ Max.
 - OPERATING TEMPERATURE:-45°C TO +110°C.
 - PRODUCT NUMBER CODE:
DS1022-02 - X X X X

Dim A type

1: 3.20	11: _____
2: _____	12: _____
3: _____	13: _____
4: _____	14: _____
5: _____	15: _____
6: _____	16: _____
7: _____	17: _____
8: _____	18: _____
9: _____	19: _____
10: _____	20: _____

CONTACT PLATING
8: Full gold flash
6: Full Tin

CONTACTS TYPE
S:SMT TYPE

No.OF CONTACTS
1*2-1*40

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5'
.X	±0.38	.X	±3'
.XX	±0.25	.XX	±2'

PROJECTION	TITLE
UNITS	PIN HEADER PITCH 2.54mm
SHEET SIZE	SINGLE ROW R/A SMT TYPE W/ POST
	SERIES DS1022-02 SERIES

RECOMMEND PCB LAYOUT
(TOLERANCE=±0.05)

DRAWING TYPE	CUSTOMER		
SCALE	1:1	SHEET	1 OF 1
DRAWING NO.	C-DS1022-02-XXXXX		